

Native IP Device

Connect to your IP network.

Simple to install and easily configured with a web browser

Power over Ethernet

Single cable deployment. No Mains required

Direct Control From NGx Consoles

Fingertip dimming and On/Off control from NGX console application.

Maintained/Non-Maintained Mode

Choice of Maintained or Non-Maintained operation.

**ALDEML3-IP**

A PoE LED fixture for emergency exit lighting applications.

The unit can be wall mounted and plugged directly into a PoE data outlet and configured over the network using a web browser.

A 3 hour battery is incorporated to operate when power failure occurs.

Discharge testing and device status can be configured and viewed via a web browser interface.



ALDEML3-IP

IP PoE Lighting Module

Technical Data

Model No:

ALDEML3-IP

Connectivity:

1 No. 10/100 Base TX Ethernet RJ45

Lumen per Watt:

66 lm/W (Dimmable)

Management/Configuration:

Web Browser

Features:

4 x Digital Inputs; 4 x Digital Outputs (switched –ve)
3 Hour emergency duration.

Integration:

Milestone XProtect
NGxVision

Power Supply:

Power over Ethernet IEEE802.3af or above
Max overall load max overall load 8W whilst maintained AND charging.

Dimensions:

390mm x 190mm x 60mm

Environment:

Environment Temperature -20 C ~ +45 C



IP Devices
Access, Security, Audio & Lighting Control

Technology House
5 Walton Rd
Pattinson North Industrial Estate
Washington
Tyne And Wear
NE38 8QE

T: +44 (0) 191 603 0000
F: +44 (0) 191 603 1000

E: sales@netgenium.co.uk
W: www.netgenium.co.uk